

Olympia Micro ClimaPlus™



Fine textured panel

Features and Benefits

- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- *CLIMAPLUS™* 15-year Lifetime System Warranty to withstand conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with USG's *Donn®* Brand Suspension Systems.

Applications

- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores

Olympia Micro Acoustical Ceilings

ClimaPlus™



UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost
	2' x4' x5/8"	Class A	4411	.50	30	.85	White	A, B	52%	\$\$
(SLT) 	2' x2' x5/8"	Class A	4221	.50	35	.85	White	D	52%	\$\$
	2' x4' x5/8"	Class A	4421	.50	35	.85	White	D	52%	\$\$
(FLB) 	2' x2' x5/8"	Class A	4231	.50	35	.85	White	E, F, G	52%	\$\$
	2' x4' x5/8"	Class A	4431	.50	35	.85	White	E, F, G	52%	\$\$
(SLT) ³ 	2' x4' x3/4"	Class A	4742	.50	35	.85	White	D	52%	\$\$
(ILT) 	2' x2' x3/4"	Class A	4744	.50	35	.85	White	E	52%	\$\$

Olympia Micro CLIMAPLUS™ Illusion Two/24 Panels The look of 2' x 2' panels

Illusion Two/24

Patterns



Grid Profile Options

A DONN® DX®/ DXL™	B DONN DXW™	C CENTRICITEE™	D DONN DX/DXL	E CENTRICITEE		

ASTM E1264 classification
Type III, Form 2, Pattern CE
ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 10

Weight
0.92 lb./ft.²
Thermal resistance
R-1.4 (5/8" panels)
R-1.7 (3/4" panels)
Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes
1. LR values are shown as averages.
2. For details, see the Recycled Content selector.
3. Panels have 15/16" routing.

SAFETY FIRST!
Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.